

Tri-Met Metal Filters & Frames




TRI-MET BAFFLE GREASE FILTERS

For use in kitchen exhaust systems

- Recommended by insurance companies
- Continuous grease drain off
- Easy to clean

Specification	Tri-Met Baffle Grease Filters
Standard depth	2" (nominal)
Construction	Galvanized, aluminum, and type 304 stainless steel
Resistance @ 175 FPM	0.133 "W.G.




TRI-MET PERMANENT METAL MESH FILTERS

For general HVAC systems

- Optional bale handles
- Custom filters available
- Easy to clean

Specification	Tri-Met Permanent Metal Mesh Filters
Standard depths	½, 1 or 2" (nominal)
Construction	Galvanized, aluminum, and stainless steel
Resistance @ 175 FPM	0.02 "W.G.
Arrestance @ 5 microns	80%
Dust holding @ 1.0 "W.G.	450 grams

Tri-Met Metal Filters & Frames




TRI-MET TMT TUCK IN PAD HOLDING FRAME

For general HVAC systems

- Galvanized, welded wire back
- Tuck-in frame
- Custom sizes
- 24-GA construction

Specification	Tri-Met TMT Pad Holding Frames
Standard depth	½, 1 or 2" (nominal)
Construction	Galvanized



TRI-MET TMZ PAD HOLDING FRAME

For general HVAC systems

- Expanded mesh
- Gate (tuck-in door)
- Custom sizes
- 24-GA construction

Specification	Tri-Met TMZ Pad Holding Frames
Standard depth	½, 1 or 2" (nominal)
Construction	Galvanized

Tri-Dim Filter Corporation is committed to continual product development - all descriptions, specifications and performance data are subject to change without notice. Tri-Dim products are manufactured to exacting criteria - there can be a ±5% variance in filter performance.

LOCAL REPRESENTATIVE