


Nanoclass Square Eco KE

Product Range




Features



Applications



Filter Class



KEY FACTS

- High efficiency across all filter classes
- Available in filter classes E11 to U16
- Integral knife-edge for use with gel-seal grid ceiling systems
- Available in depths of 86, 109 and 134 mm
- Minipleat technology for laminar flow
- Low pressure drop
- Guaranteed leak free

DESIGN

Filter medium constructed from various grades of microglass fiber paper folded into a pack. As standard, the pack is sealed into an anodized aluminum frame with integrated knife-edge.

APPLICATIONS

Final filter for clean rooms and clean workbenches that use gel-seal grid systems. For separation of viruses, bacteria, toxic dust and aerosols, in hospitals/medical institutes, chemists, laboratories, clean rooms, pharmacy, food processing industry, microelectronics.

Nanoclass Square Eco

KE

PERFORMANCE DATA

Filter Class	Dimensions	Flow Rate	Pressure Drop
EN 1822	mm	m ³ /h	Pa
H13	305 x 305 x 109	150	90
H13	305 x 610 x 109	300	90
H13	305 x 762 x 109	375	90
H13	305 x 915 x 109	450	90
H13	457 x 457 x 109	350	90
H13	457 x 610 x 109	450	90
H13	610 x 610 x 109	600	90
H13	610 x 762 x 109	750	90
H13	610 x 915 x 109	900	90
H13	610 x 1220 x 109	1200	90
H13	762 x 1220 x 109	1500	90
H13	762 x 915 x 109	1130	90
H13	1220 x 1220 x 109	2400	90

Filter Class	Dimensions	Flow Rate	Pressure Drop
EN 1822	mm	m ³ /h	Pa
H14	305 x 305 x 109	150	100
H14	305 x 610 x 109	300	100
H14	305 x 762 x 109	375	100
H14	305 x 915 x 109	450	100
H14	457 x 457 x 109	350	100
H14	457 x 610 x 109	450	100
H14	610 x 610 x 109	600	100
H14	610 x 762 x 109	750	100
H14	610 x 915 x 109	900	100
H14	610 x 1220 x 109	1200	100
H14	762 x 915 x 109	1130	100
H14	762 x 1220 x 109	1500	100
H14	1220 x 1220 x 109	2400	100

SPECIFICATION

Recommended air flow	Flow rate \pm 10 %	Recommended final pressure drop	450 Pa (max. 600 Pa)
Heat resistance	Up to 70 °C (Peak 90 °C)	Moisture resistance	100 % rel. humidity
Regenerable	No	Incinerable	No

OPTIONS

Gasket	Continuous polyurethane foam or flat neoprene
Grid	1 or 2 sides