

Airpanel Select FZL

Product Range



Applications



Filter Class



KEY FACTS

- Self-stable, synthetic filter medium
- Several frame types available
- Easy assembly and handling
- Maintenance-friendly

DESIGN

Pleated, synthetic filter medium, self-stable design, pleats are separated by hotmelt spacers to ensure stability.

APPLICATIONS

Prefiltration for air-conditioning and ventilation equipment and/or systems, highly effective with coarse dust.

OPTIONS

Frame	Polyester, metal or plastic
Gasket	Foamed polyurethane continuous gasket

Airpanel Select FZL

PERFORMANCE DATA

Filter Class		Dimensions	Flow Rate	Pressure Drop
ISO 16890	EN 779	mm	m ³ /h	Pa
Coarse 70%	G4	285 x 592 x 24	475	35
Coarse 70%	G4	492 x 592 x 24	825	35
Coarse 70%	G4	492 x 622 x 24	875	35
Coarse 70%	G4	592 x 592 x 24	1000	35
Coarse 70%	G4	285 x 592 x 46	950	35
Coarse 70%	G4	492 x 492 x 46	1375	35
Coarse 70%	G4	492 x 592 x 46	1650	35
Coarse 70%	G4	492 x 622 x 46	1750	35
Coarse 70%	G4	592 x 592 x 46	2000	35
Coarse 70%	G4	285 x 285 x 96	650	35
Coarse 70%	G4	395 x 622 x 96	2075	35
Coarse 70%	G4	492 x 622 x 96	2550	35
Coarse 70%	G4	592 x 592 x 96	2900	35
Coarse 80%	M5	285 x 592 x 46	950	45
Coarse 80%	M5	492 x 492 x 46	1375	45
Coarse 80%	M5	492 x 592 x 46	1650	45
Coarse 80%	M5	492 x 622 x 46	1750	45
Coarse 80%	M5	592 x 592 x 46	2000	45
Coarse 80%	M5	285 x 285 x 96	650	45
Coarse 80%	M5	395 x 622 x 96	2075	45
Coarse 80%	M5	492 x 622 x 96	2550	45
Coarse 80%	M5	592 x 592 x 96	2900	45

SPECIFICATION

Recommended air flow	Flow rate ± 25 %	Rec. final pressure for efficient energy use acc. to EN 13053	Lowest value of initial pressure drop + 50 Pa, or initial pressure drop x 3
Heat resistance	Max. 70 °C	Moisture resistance	100 % rel. humidity
Regenerable	No	Incinerable	Yes, except for metal frames