

Airroll Pro Paint NoGlass

Product Range



Features



Applications



Filter Class

G

Coarse



KEY FACTS

- Contains no irritants
- Zero risk of shedding
- Last up to four times longer than equivalent glass media
- Suitable for heavy-duty use
- High dust and paint holding capacity

DESIGN

Constructed from robust, flexible, polyester fibers connected by strong bonds, with no risk of shedding.

APPLICATIONS

Designed for paint booth and other wet/dry applications.

Airroll Pro

Paint NoGlass

PERFORMANCE DATA

Filter Class		Dimensions	Air Velocity	Pressure Drop
ISO 16890	EN 779	mm	m/s	Pa
Coarse 70%	G4	750 x 20000 x 30	1.5	≤22
Coarse 70%	G4	1000 x 20000 x 30	1.5	≤22
Coarse 70%	G4	2000 x 20000 x 30	1.5	≤22
Coarse 70%	G4	750 x 20000 x 40	1.5	≤30
Coarse 70%	G4	1000 x 20000 x 40	1.5	≤30
Coarse 70%	G4	2000 x 20000 x 40	1.5	≤30
Coarse 70%	G4	750 x 20000 x 50	1.5	≤35
Coarse 70%	G4	1000 x 20000 x 50	1.5	≤35
Coarse 70%	G4	2000 x 20000 x 50	1.5	≤35

SPECIFICATION

Recommended air velocity	2 m/s	Rec. final pressure for efficient energy use acc. to EN 13053	Lowest value of initial pressure drop + 50 Pa, or initial pressure drop x 3
Heat resistance	Max. 70 °C	Moisture resistance	100 % rel. humidity
Regenerable	No	Incinerable	Yes